

Cod. 10504

Macchine semoventi



# Reflex

Cannone ad impulsi di medio-grande portata



Peso netto	Connessione	Dimensioni	Ugello	Angolo
<b>10,5 kg</b>	<b>6 x 130 mm (M8)</b>	<b>ø 1676 mm x 557 mm</b>	<b>Ø 16 ÷ 36 mm</b>	<b>25°</b>

Pressione

Ugello	3 bar		4 bar		5 bar		6 bar		7 bar	
	Portata	Gittata	Portata	Gittata	Portata	Gittata	Portata	Gittata	Portata	Gittata
	l/min	m	l/min	m	l/min	m	l/min	m	l/min	m
<b>16 mm</b>	276	32,5	320	36,5	356	39,5	391	42,5	-	-
<b>18 mm</b>	350	34,0	404	38,0	452	42,0	496	44,5	-	-
<b>20 mm</b>	432	36,0	501	40,0	560	44,0	613	47,0	-	-
<b>22 mm</b>	522	38,5	604	42,5	676	46,0	741	49,5	-	-
<b>24 mm</b>	623	40,0	720	44,5	806	49,0	882	52,5	-	-
<b>26 mm</b>	732	41,0	846	46,0	946	50,0	1037	54,0	-	-
<b>28 mm</b>	848	43,0	981	48,0	1096	52,0	1202	56,0	-	-
<b>30 mm</b>	974	44,5	1127	50,0	1260	54,0	1381	58,0	-	-
<b>32 mm</b>	-	-	1282	52,0	1433	56,0	1570	59,5	1694	63,0
<b>34 mm</b>	-	-	1448	54,0	1619	57,5	1774	61,0	1913	65,0